

LUPHOScan⁵⁰ SL



The world's fastest and most accurate system,
for non-contact 3D cellphone lens metrology.

LUPHOScan SL

Ultra fast, non-contact, 3D form measurement

Measure cellphone lenses in <60 seconds

Based on the industry standard LUPHOScan platform

Introducing the LUPHOScan SL with new probe technology for increased measurement flexibility and ultra fast measurement times down to < 60 seconds.

The LUPHOScan SL is ideal for high volume production of small lenses with key benefits of the system including ultra fast measurement speeds and the ability to measure geometric lens features.

Unique benefits for both design and production.

- **Ultra high, repeatable accuracy**
≤ 30 nm PV (3σ)
- **Best available stability**
Power variation < ± 15 nm (3σ),
PV variation < ± 1.5 nm (3σ)
- **Analyse geometric features**
Such as interlocks and edge diameters in relation to each other or the optical surface
- **Thin transparent substrates**
Down to 100 μ m thickness
- **Fast measurement speeds for true 3D**
< 120 sec. - Optical surface and geometric features*
< 60 sec. - Optical surface only**




Measurement principle

During measurement the probe performs a spiral scan over the entire surface of the object under test and produces high density 3D data.

Scanning is achieved by rotating the object by means of an air-bearing spindle whilst the sensor is moved radially and axially using linear stages.

A rotary stage keeps the sensor normal to the object surface. The layout of movement stages provides high flexibility, even for uncommon surface shapes including steep slopes or profiles with points of inflection.



Movement of the LUPHOScan object sensor

* Such as surface flats, interlocks and edge diameters.
** Geometry and lateral resolution dependant.

“


Advanced capability delivers world's fastest measurement of 3D surface and interlocks

< 120 sec. cycle time




”



New 7.5 mm working distance prevents collision



Reference frame and layout of probe stages (R, Z, T) and object stage (C)




Improve quality and yield with real full 3D measurement results showing true form errors

Optimised LUPHOScan probe.

The new probe technology used on the LUPHOScan SL adds additional benefits including an increased working distance of 7.5 mm.

This enables complex geometric features on lens moulds and moulded lenses to be measured, such as:




- Access to measure interlocks without collision between the probe and substrate.
- Increased access to steep concave optical surfaces



Improve measurements of interlocks without collision

Lens form metrology

Increased yield and quality with true 3D accuracy
3D measurement & analysis in < 60 seconds



Fully automated analysis options for professional reporting.

2D extracted profiles with 'Max Form Error' feature.

Form error results can be automatically optimised to output the maximum form error present on a part.

Only true 3D measurements can provide this level of form error information.

The example shown identifies that the same 3D form error can yield two completely different 2D form errors.





3D measurement with 3D surfaces for in-depth reporting.

Measurement results can be output showing the complete surface form error with the 3D option, including extracted 2D profiles.

- ISO compliant analysis results (ISO 10110).
- Auto export results for quality control and traceability.
- Export 3D measured surface in common formats for process improvement.
- Set pass/fail criteria for easy process control.

Advanced lens metrology

Increased productivity with world's fastest measurement
3D optical surface & interlocks in < 120 seconds



Fast measurement and analysis of the optical surface and geometrical features.

Measure the optical surface and geometrical features such as interlock surface roundness, flatness of the flat lens surface and location of the optical surface relative to these features.

Optical surface is off centre and tilted relative to the interlock feature position and lens flange.

The analysed results (A) show the lens form error of the optical surface relative to the interlock and lens flange.

The results highlight the real form error which would be seen if the lens had been put into an assembly and aligned relative to these features.

The optical surface (B) shows the tilt compensated form error.



Typical cellphone lens assembly

Tooling system

Simple tooling system for increased throughput

Rapid set-up with no alignment required


Save time with easy part set-up and measurement.

The easy-to-use tooling enables accurate measurements with simple set-up.

1. LUPHOScan SL system with tooling chuck
2. Dedicated lens mount.
3. Lens loaded into lens mount.
4. Lens measurement using LUPHOScan SL, lens mount and tooling chuck.




Tray of multiple lens holders, enabling fast changing



Critical results, trust Taylor Hobson.

Easy, fast & accurate calibration.

- High quality calibration with 3 artefacts (included as standard).
- Calibration artefact compatible with tooling chuck
- Easy-to-use interface with no alignment required.
- Complete calibration cycle takes only 15 minutes



The Metrology Experts

Established in 1886, Taylor Hobson is the world leader in surface and form metrology and developed the first roundness and surface finish measuring instruments.

www.taylor-hobson.com

Sales department

Email: taylor-hobson.sales@ametek.com

Tel: +44 (0) 116 276 3771

- **Design engineering** – special purpose, dedicated metrology systems for demanding applications.
- **Precision manufacturing** – contract machining services for high precision applications and industries.

Centre of Excellence department

Email: taylor-hobson.cofe@ametek.com

Tel: +44 (0) 116 276 3779

- **Inspection services** – measurement of your production parts by skilled technicians using industry leading instruments in accord with ISO standards.
- **Metrology training** – practical, hands-on training courses for roundness and surface finish conducted by experienced metrologists.
- **Operator training** – on-site instruction will lead to greater proficiency and higher productivity.
- **UKAS calibration and testing** – certification for artifacts or instruments in our laboratory or at customer's site.

Service department

Email: taylor-hobson.service@ametek.com

Tel: +44 (0) 116 246 2900

- **Preventative maintenance** – protect your metrology investment with an AMECare support agreement.



© Taylor Hobson Ltd. 2019



Taylor Hobson UK

(Global Headquarters)

PO Box 36, 2 New Star Road
Leicester,
LE4 9JQ,
England

Tel: +44 (0)116 276 3771
taylor-hobson.sales@ametek.com



Taylor Hobson France

Rond Point de l'Épine Champs
Batiment D, 78990 Elancourt, France

Tel: +33 130 68 89 30
taylor-hobson.france@ametek.com



Taylor Hobson Germany

Rudolf-Diesel-Straße 16,
D-64331 Weiterstadt, Germany

Tel: +49 6150 543 0
taylor-hobson.germany@ametek.com



Taylor Hobson Italy

Via Della Liberazione 24, 20068, Peschiera
Borromeo, Zelofoaramagno, Milan, Italy

Tel: +39 02 946 93401
taylor-hobson.italy@ametek.com



Taylor Hobson India

Divyasree NR Enclave, 4th Floor, Block A,
Plot No. 1, EPIP Industrial Area, Whitefield,
Bengaluru - 560066, India

Tel: +91 80 6782 3346
taylor-hobson.india@ametek.com



Taylor Hobson China

taylor-hobson-china.sales@ametek.com

Shanghai Office

Part A1, A4, 2nd Floor, Building No. 1, No. 526
Fute 3rd Road East, Pilot Free Trade Zone,
Shanghai, 200131, China

Tel: +86 21 5868 5111-110

Beijing Office

Western Section, 2nd Floor, Jing Dong Fang
Building (B10), No. 10, Jiu Xian Qiao Road,
Chaoyang District, Beijing, 100015, China

Tel: +86 10 8526 2111

Chengdu Office

No. 9-10, 10th floor, 9/F, High-tech Incubation
Park, No. 160, Jinyue West Road, Chengdu
610041, China

Tel: +86 28 8675 8111

Guangzhou Office

Room 810 Dongbao Plaza, No.767 East
Dongfeng Road, Guangzhou, 510600, China

Tel: +86 20 8363 4768



Taylor Hobson Japan

3F Shiba NBF Tower; 1-1-30, Shiba Daimon
Minato-ku, Tokyo 105-0012, Japan

Tel: +81 34400 2400
taylor-hobson.japan@ametek.com



Taylor Hobson Korea

#309, 3rd FL, Gyeonggi R&DB Center; 105,
Gwanggyo-ro, Yeongtong-gu, Suwon-si,
Gyeonggi-do, Korea, 16229

Tel: +82 31 888 5255
taylor-hobson.korea@ametek.com



Taylor Hobson Singapore

AMETEK Singapore, 10 Ang Mo Kio Street 65,
No. 05-12 Techpoint, Singapore 569059

Tel: +65 6484 2388 Ext 120
taylor-hobson.singapore@ametek.com



Taylor Hobson Thailand

89/45, Moo 15, Enterprise Park, Bangna-Trad
Road, Tambol Bangkaew, Amphur Bangplee,
Samutprakarn Province 10540, Thailand

Tel: +66 2 0127500 Ext 505
taylor-hobson.thailand@ametek.com



Taylor Hobson Taiwan

10F-5, No.120, Sec. 2, Gongdao Wu Rd.,
Hsinchu City 30072, Taiwan

Tel: +886 3 575 0099 Ext 301
taylor-hobson.taiwan@ametek.com



Taylor Hobson Mexico

Acceso III No. 16 Nave 3 Parque Ind. Benito
Juarez Queretaro, Qro. Mexico C.P. 76120

Tel: +52 442 426 4480
taylor-hobson.mexico@ametek.com



Taylor Hobson USA

27755 Diehl Road, Suite 300, Warrenville,
IL 60555, USA

Tel: +1 630 621 3099
taylor-hobson.usa@ametek.com



1100 Cassatt Road, Berwyn, PA 19312, USA
Email: info.corp@ametek.com
Web: www.ametek.com